## NOTES

- 1. LOCATE UNDERGROUND UTILITIES PRIOR TO DIGGING. CALL USA (UNDERGROUND SERVICE ALERT) 1-800-277-2600, MON THRU FRI 6AM TO 7PM, A MINIMUM 2 WORKING DAYS WITH A MAXIMUM 14 CALENDAR DAYS, TO OBTAIN A TICKET. CONTACT THE DISTRICT INSPECTOR OR PARK SUPERVISOR FOR DISTRICT UTILITIES NOT LOCATED BY USA.
- 2. CONCRETE SHALL BE COMMERCIAL 5-SACK PRE-MIX CONCRETE OR EQUIVALENT.
- 3. SIGN POLE SHALL BE INSTALLED PLUMB AT CENTER OF CONCRETE FOOTING.
- 4. STEEL PIPE SIGN POSTS TO BE USED FOR REGULATORY SIGNS IN STREETS AND PARKING AREAS U.O.N.
- 5. COAT CUT END OF PIPE WITH THICK COAT OF ZINC RICH PAINT MEETING THE REQUIREMENTS OF ASTM A780. MATCH SILVER POST COLOR.
- 6. THE BOTTOM OF THE LOWEST SIGN PANEL SHALL BE A MINIMUM OF 80" ABOVE THE SURROUNDING SURFACE GRADE, EXCEPT THAT SIGNS INSTALLED OUTSIDE OF TRAVEL ROUTES, SUCH AS IN A PLANTER, MAY BE LOWERED TO 72" ABOVE SURROUNDING SURFACE GRADE. SPECIAL CONDITIONS, SUCH AS ACCESSIBLE PARKING SIGNS AND TREADLE WARNING SIGNS, SUPERSEDE THESE TYPICAL REQUIREMENTS.

