



**NOTES:**

1. WIRE MESH CYLINDER SHALL BE FABRICATED FROM 1-INCH, HEXAGONAL PATTERN, 20-GAUGE MESH WIRE.
2. WIRE EDGE AT TOP OF CYLINDER SHALL BE THE MANUFACTURED FINISHED EDGE. OTHER WIRE EDGES THAT ARE CUT MUST BE FREE OF SHARP POINTS.
3. SUPPORT STAKES SHALL BE 2-INCH NOMINAL DIAMETER OR 2 X 2-INCH NOMINAL SIZE WOOD STAKES A MINIMUM OF 5- FEET LONG.
4. JUTE MESH COVER SHALL BE UNBLEACHED, UNDYED, DEGRADABLE, OPEN WEAVE TEXTILE (OWT), RATED FOR 12 MONTHS, 14-20 STRANDS PER FOOT (MIN IN EA DIRECTION), MIN WEIGHT 14.4-19.2 OZ/SQ YD.
5. TWINE SHALL BE 1/8-INCH DIA MANILA HEMP TWINE.
6. FASTENERS SHALL BE 1/2" LEG X 3/8" CROWN GALVANIZED STEEL STAPLES, T50 OR EQUAL.



**FOLIAGE PROTECTOR**

DRAWN	CR	KEY	REVISIONS	DATE	APPROVED
CHECKED	RB	△	ORIGINAL ISSUE	06-14-16	<i>[Signature]</i>
OPERATIONS	DC				ROB LIM, PE, CHIEF OF DESIGN & CONSTRUCTION
					DATE 6/27/16

STD PLAN

**604**

SHEET 1 OF 1  
NOT TO SCALE